





intimus 120 In the Department

Professional Data Shredders – a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.

- Low noise level
- Integrated Auto Reverse Function for easy removal of paper iams
- Illuminated indicators for stand-by, basket full, door open and paper jam
- Sealed dust-free design with robust wooden cabinet
- Mounted on rollers for flexible use



















	Shred size	111	m	Security level DIN 66 399				Shredding capacity* sheets		Throughput** sheets/min		Also shreds: in 8 mm strip cut						
Model	mm	- 1		P	F	0	Т	Н	E	70 g/m ²	80 g/m ²	m/s	70 g/m ²	80 g/m ²	y	6		
120 SC2	5.8	120	5+	2	-	1	2+	-	-	35-38	33-36	0.14	1,030	975	✓	✓	✓	✓
120 SC2	3.8	120	5+	2	-	1	2+	-	-	31-33	29-31	0.14	905	865	✓	✓	✓	✓
120 CC3	3.8 x 36	120	5+	4	1	1	2+	-	-	23-25	21-23	0.14	680	625	✓	✓	✓	✓
120 CC4	1.9 x 15	120	5+	5	2	1	2+	-	-	15-17	13-15	0.14	455	410	✓	✓	✓	✓
⁺only floppy disks / ID cards																		
High Security Shredder (optionally available with automatic oiler)																		
120 CC5	0.8 x 12	120	5+	6	3	-	-	-	-	10-12	8-10	0.14	313	256	-	-	-	_
120 CC6	0.8 x 4.5	120	5+	7*	3	_	-	-	-	7-8	6-7	0.14	214	185	-	-	-	-
* NSA approved (NSA / CSS EPL 02/01)																		

Optional Equipment	Packing unit	Art. No.
PE bags intimus 100 and 120	50 pieces	99977

Shredder oil for CC-models	Packing unit	Art. No.		
Bottle at 110 ml	6 bottles	88035		
for models with oiler, 2 litres	1 canister	91869		

^{*} based on 70 g/m2 A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.

^{**} theoretical average performance paper/min