

TECHNICAL DESCRIPTION

MOD.PRONTO

"PRONTO" is a family of phonebooths designed for meeting, operational work or private conversation.

The small size gives lightness and versatility, qualities that make them easy to position and adapt to any place.

They are available in two types:

- with fixed window
- with blind panels

MATERIAL DESCRIPTION

EXTERNAL

The supporting structure: is made of MATT BLACK RAL 9004 painted iron.

External panels: made with particleboard panels th. 18 mm faced in melamine (Class E1 low Formaldehyde content) and edged on the perimeter in ABS thick 2 mm matching the surface and available in the colours: OAK 03, CLASSIC WALNUT 07, NATURAL OAK 09, MODERN WALNUT 13, MOSS 20, NIAGARA OAK 31, GREY 38, GRANADE RED 39, SAGE GREEN 40, MISTY BLUE 41, STONE GREY 44, ANTIQUE PINK 46, BLACK 59, DARK POPLAR 63, LIGHT POPLAR 64, WHITE 68.

Door and window: made with BLACK painted extruded aluminum profile, 3+3 mm laminated transparent glass, BLACK color zamak handle.

INTERNAL

Floor: in particleboard panel thick 25 mm covered with GREY carpet. Adjustable feet are inserted on the base.

Ceiling made up of: external cover in ABS thick 3 mm, 2 fiber panels thick 25+30 mm 50 kg/mc with interposed high density rubber thick 5 mm, internal lining in felt thick 3mm.

Internal walls: made with particleboard panels thick 18 mm melamine faced (Class E1 low Formaldehyde content) with acoustic sponge thick 5 mm covered in fire-retardant STRETCH fabric, available in the following colours: IVORY 585, GREY 586, ANTHRACITE 587, BLACK 588, GREY BEIGE 589, BROWN 590, ACID GREEN 591, WOOD GREEN 592, SKY BLUE 593, BLUE 594, FREESIA YELLOW 595, ORANGE 596, RED 597, AMARANTH 598.

Shelf: made with particleboard panel thick mm 35 faced in melamine (Class E1 low Formaldehyde content) and edged on the perimeter in ABS mm 2 matching the surface and available in the colours: OAK 03, CLASSIC WALNUT 07, STONE GREY 44, BLACK 59, DARK POPLAR 63, LIGHT POPLAR 64, WHITE 68.

The front corners are rounded and on the surface there is a hole with charger USB socket with 2 connections type A.

Fixing takes place with two retractable type supports.

Standard equipment:

LED light, fan, presence sensor; USB output.LED Lighting:

Light Beam 120°

Certifications: CE - UL

Dimensions: 563x21xH10 mm

IP Protection : IP20

Voltage: 12V DC

Power input: 10 W/mt

frequency: 50-60 Hz

Frame Color: Grey Anodized

Color Temperature: 4000 K

Motion Sensor:

Dimensions: Ø24,3mm H18,8mm

Certifications: CE & RoHS

Voltage: 100-240V

Frequency: 50 Hz

Detection Angle: 80°

Power input: 0,5 W

IP Protection: IP20

Time Adjustment : 10 sec-3 min

Lux Adjustment : 5-1000 lux

Fan:

Dimensions: 120x120xH25 mm

Certifications: CE TUV CUR UL

Ventilation perf .: 75 CFM 127 m³/h

Noise Level: 34 dB

Rotation Speed: 2200 RPM

Voltage: 24 VDC

Power input: 2,0 W

Charger USB socket with 2 Connections type A:

Dimensions: Ø 35mm H29,5mm

Input: 12V DC 2.0 AMP

Output: 5 V max

Released by the Technical Office of LAS MOBILI

last revision date: JUNE 2023